

34394 ALD-LL-WW-MAT-S-PT

Linear LED luminaire

5905339343949



GENERAL DATA:

Colour: silver

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object : 0,5m

Compatible with a dimmer: DALI

Fixture lighting direction: down

Length [mm]: 1710

Width [mm]: 83

Height [mm]: 65

Integrated LED light source : yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 33

Class of protection against electric shock : I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 4100

Colour temperature: Warm white

Correlated colour temperature [K]: 3000

Colour consistency in McAdam ellipses : ≤3

Colour rendering index: 80

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :
L90B10

Number of on/off cycles : ≥30000

Lighting angle [°]: X85/Y95

Luminous efficiency of the lamp [lm/W]: 124

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: matt

Enclosure material: steel

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5÷2,5

Lamp-heating time [s]: ≤1


Lamp-ignition time [s]: ≤0,5

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1



Linear LED luminaire

Number of units in the secondary packaging : 1

Number of units in the packaging : 1

Net unit weight [g] : 2400

Grammage [g] : 2840

Length of a unit pack [cm] : 182

Width of a unit pack [cm] : 11

Height of a unit pack [cm] : 7

Weight of a cardboard box [kg] : 2.84

Width of a cardboard box [cm] : 11

Height of a cardboard box [cm] : 7

Length of a cardboard box [cm] : 182

Volume of a cardboard box [m³] : 0.014014

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website