

## 35003 STIVI LED 36W-NW-O-SE

Ceiling-mounted LED light fitting

5905339350039



The Kanlux STIVI LED ceiling light will provide you with lighting where standard luminaires may fail. It is characterised by high luminous efficacy of 130lm/W, a high level of protection - IP65 and impact protection rating of IK08. Kanlux STIVI LED luminaire can be used outdoors (on balconies, terraces, patios, open arbours), in corridors and staircases, as well as in places with increased humidity (laundry rooms, changing rooms and passageways at swimming pools). Additional advantages include: 5-year warranty and 50,000 hours of light source life in the luminaire, as well as the option of choosing a version with a motion sensor. We recommend it as a high-end investment product or for professional domestic use.

### GENERAL DATA:


**Colour:** white  
**Place of assembly:** wall mounted, ceiling mounted  
**Place of application:** Indoors and outdoors  
**Micro-interval between relay contacts:** yes  
**Minimum distance from the illuminated object:** 0,5m  
**Possibility of fixture-loop-through connection:** yes  
**Compatible with a dimmer:** no  
**Wykrywanie ruchu:** yes  
**Height [mm]:** 54  
**Diameter [mm]:** 330  
**Sensitivity regulation:** yes  
**Mercury content:** no  
**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 36  
**Class of protection against electric shock:** II  
**Lampshade material:** PC  
**Diode type:** LED SMD  
**Luminous flux of the light fitting [lm]:** 4680  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** 6000  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** in sphere (360°)  
**Colour temperature:** white  
**Correlated colour temperature [K]:** 4000  
**Colour consistency in McAdam ellipses:**  $\leq 6$   
**Colour rendering index:** 80  
**Service life [h]:** 50000

## 35003 STIVI LED 36W-NW-O-SE

Ceiling-mounted LED light fitting



**Number of on/off cycles:**  $\geq 30000$

**Lighting angle [°]:** 110

**Luminous efficiency of the lamp [lm/W]:** 130

**Ambient temperature range to which the product can be exposed:**  $-20 \div 40$

**Enclosure material:** PC

**Sensor type:** microwave

**Connection type:** Self-clamping block

**Range of sections of wires used [mm<sup>2</sup>]:** 0,5-2,5

**Sensor-operation time [second-minute]:** 5-15

**Lamp-heating time [s]:**  $\leq 1$

**Lamp-ignition time [s]:**  $\leq 0,5$

**Sensor-operation frequency [MHz]:** 5800

**sensor working angle [°]:** H360

**Illumination-level setpoint by which the sensor detects movement [lx]:** 2/10/50/off

**IK class:** 08

**IP class:** 65

**Sensor range[m]:** max 3

### LOGISTIC DATA:

**Packaging method:** 8

**Number of units in the packaging:** 8

**Net unit weight [g]:** 1040

**Grammage [g]:** 1326.25

**Length of a unit pack [cm]:** 34

**Width of a unit pack [cm]:** 6.5

**Height of a unit pack [cm]:** 34

**Weight of a cardboard box [kg]:** 10.61

**Width of a cardboard box [cm]:** 36


**Height of a cardboard box [cm]:** 36

**Length of a cardboard box [cm]:** 54

**Volume of a cardboard box [m<sup>3</sup>]:** 0.069984

### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website



## 35003 STIVI LED 36W-NW-O-SE

Ceiling-mounted LED light fitting

