

## **35678** TIBERI PRO NT30W-940W

Downlight fitting

5905339356789





















Kanlux TIBERI PRO NT is a family of surface-mounted downlights. They are available in two wattages (20W and 30W) and two colors (white and black) while keeping the same size. The Kanlux TIBERI PRO luminaire is primarily characterized by high tightness (IP54) and high color rendering index (Ra> 90), but also easy installation on the ceiling using a bracket. The Kanlux TIBERI PRO NT luminaire is a high quality component confirmed by a 5-year warranty.

#### **GENERAL DATA:**

Colour: white

Place of assembly: ceiling mounted Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Height [mm]: 113 Diameter [mm]: 170

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 30

Class of protection against electric shock: |

Lampshade material: plastic

Diode type: LED SMD Luminous flux [Im]: 3000 Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 90 Service life [h]: 50000

Number of on/off cycles: ≥30000


Lighting angle [°]: 115


Luminous efficiency of the lamp [lm/W]: 100

**Enclosure material**: aluminum alloy **Connection type**: Free cable ends

Wire length [m]: 0.18Wire diameter [mm<sup>2</sup>]: 0.75Lamp-heating time [s]:  $\le 1$ Lamp-ignition time [s]:  $\le 0.5$ 

IP class: 54









# **35678** TIBERI PRO NT30W-940W

### Downlight fitting

### LOGISTIC DATA:

Packaging method: 12

Number of units in the secondary packaging: 1

Number of units in the packaging: 12

Net unit weight [g]: 1162 Grammage [g]: 1323.33


Length of a unit pack [cm]: 17.5 Width of a unit pack [cm]: 17.5 Height of a unit pack [cm]: 12.5

Weight of a cardboard box [kg]: 15.87996

Width of a cardboard box [cm]: 37 Height of a cardboard box [cm]: 28 Length of a cardboard box [cm]: 54.5 Volume of a cardboard box [m³]: 0.056462

### **ADDITIONAL INFORMATION:**

• 5 years Warranty under the terms of the warranty statement, available on our website



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

