

36136 OS-L5D-WN-RST-B-P1

Recessed - Mounted LED Office Fixture

5905339361363




















GENERAL DATA:

Colour: black

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating

material: yes Length [mm]: 595 Width [mm]: 595 Height [mm]: 34

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 31W

Class of protection against electric shock: I

Lampshade material: plastic Diode type: LED SMD

Luminous flux of the light fitting [lm]: 3800 Colour temperature: neutral warm white Correlated colour temperature [K]: 3500 Colour consistency in McAdam ellipses: ≤3

Colour rendering index: 80 Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :

L90B10

Number of on/off cycles: ≥30000

Lighting angle [°]: 50

Ambient temperature range to which the product can be

exposed: 5÷25 **Shade type**: louvre

Enclosure material: Metal

Connection type: Self-clamping block

Range of sections of wires used [mm²]: $1,5 \div 2,5$

Lamp-heating time [s]: ≤1 Lamp-ignition time [s]: ≤0,5 Rodzaj soczewki [°]: 50


IP class: 20 **UGR**: ≤15





36136 OS-L5D-WN-RST-B-P1

Recessed - Mounted LED Office Fixture



LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1


Number of units in the secondary packaging: 1


Number of units in the packaging: 1

ADDITIONAL INFORMATION:

• 5 years Warranty under the terms of the warranty statement, available on our website







We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

