


36291 KMCCB-F-200A

Wyłącznik kompaktowy MCCB

5905339362919



GENERAL DATA:

Utilisation category: A

Place of assembly: mounting plate

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 200

Rated frequency [Hz]: 50

Connection type: Terminal block

Control type: mechaniczne

Rated breaking voltage U_e [V]: 380/415; 220/230

IP class: 20

Rated insulation voltage U_i [V]: 800

Rated impulse withstand voltage U_{imp} [V]: 8000

Number of poles: 3

Znamionowa graniczna zwarciova zdolność łączeniowa I_{cu} :

36kA (380/415V AC); 50kA (220/230V AC)

Prąd znamionowy wyłączalny zwarciovy roboczy I_{cs} : 27kA

(380/415V AC); 36kA (220/230V AC)

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 12

Number of units in the secondary packaging : 1

Number of units in the packaging : 12

Net unit weight [g]: 1654

Grammage [g]: 1766.67

Gross unit weight [g]: 1728

Length of a unit pack [cm]: 17

Width of a unit pack [cm]: 11.5

Height of a unit pack [cm]: 11

Weight of a cardboard box [kg]: 21.20004

Width of a cardboard box [cm]: 37.5

Height of a cardboard box [cm]: 24.5

Length of a cardboard box [cm]: 37

Volume of a cardboard box [m³]: 0.033994

ACCESSORIES

36294

KMCCB-F-125A/AL/L styk alarmowy

36291 KMCCB-F-200A

Wyłącznik kompaktowy MCCB



36293

KMCCB-F-125A/AX/L styk pomocniczy



36303

KMCCB-F-125A/RL/R wyzwalacz napięciowy



36296

KMCCB-F-125A/UV wyzwalacz podnapięciowy



36298

KMCCB-F-250A/AL/L styk alarmowy



36297

KMCCB-F-250A/AX/L styk pomocniczy



36306

KMCCB-F-250A/RL/R wyzwalacz napięciowy

36291 KMCCB-F-200A

Wyłącznik kompaktowy MCCB



36300

KMCCB-F-250A/UV

wyzwalacz
podnapięciowy

