


## 36292 KMCCB-F-250A

Wyłącznik kompaktowy MCCB

5905339362926



### GENERAL DATA:

Utilisation category: A

Place of assembly: mounting plate

### TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 250

Rated frequency [Hz]: 50

Connection type: Terminal block

Control type: mechaniczne

Rated breaking voltage  $U_e$  [V]: 380/415; 220/230

IP class: 20

Rated insulation voltage  $U_i$  [V]: 800

Rated impulse withstand voltage  $U_{imp}$  [V]: 8000

Number of poles: 3

Znamionowa graniczna zwarciova zdolność łączeniowa  $I_{cu}$  :

36kA (380/415V AC); 50kA (220/230V AC)

Prąd znamionowy wyłączalny zwarciovy roboczy  $I_{cs}$  : 27kA

(380/415V AC); 36kA (220/230V AC)

### LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 12

Number of units in the secondary packaging : 1

Number of units in the packaging : 12

Net unit weight [g] : 1696

Grammage [g] : 1808.33

Gross unit weight [g] : 1758

Length of a unit pack [cm] : 17

Width of a unit pack [cm] : 11.5

Height of a unit pack [cm] : 11

Weight of a cardboard box [kg] : 21.69996

Width of a cardboard box [cm] : 37.5

Height of a cardboard box [cm] : 24.5

Length of a cardboard box [cm] : 37

Volume of a cardboard box [m<sup>3</sup>] : 0.033994

### ACCESSORIES

36294

KMCCB-F-125A/AL/L styk alarmowy

## 36292 KMCCB-F-250A

Wyłącznik kompaktowy MCCB



**36293**

KMCCB-F-125A/AX/L styk pomocniczy



**36303**

KMCCB-F-125A/RL/R wyzwalacz napięciowy



**36296**

KMCCB-F-125A/UV wyzwalacz podnapięciowy



**36298**

KMCCB-F-250A/AL/L styk alarmowy



**36297**

KMCCB-F-250A/AX/L styk pomocniczy



**36306**

KMCCB-F-250A/RL/R wyzwalacz napięciowy

## 36292 KMCCB-F-250A

Wyłącznik kompaktowy MCCB



36300

KMCCB-F-250A/UV

wyzwalacz  
podnapięciowy

