


Downlight fitting

5905339365125













Kanlux TAVO LED is a family of flush-mounted downlights. They are available in two shapes (round and square) and 5 wattages from 5W to 24W. Kanlux TAVO LED downlights are characterised by a minimalist, Scandinavian design. Additional advantages are their IP44/20 tightness, as well as the possibility of surface mounting the 12W and 18W models in the Kanlux TAVO FRAME.

GENERAL DATA:

Colour: white Place of assembly: Recessed mount in the ceiling Place of application: Indoors Minimum distance from the illuminated object: 0,5m Compatible with a dimmer: no The product is not suitable to be covered with a heatinsulating material: yes Height [mm]: 26 Diameter [mm]: 145 Assembly hole [mm]: Ø120 Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 12 Class of protection against electric shock: || Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 1250 Colour temperature: white Correlated colour temperature [K]: 4000 **Colour consistency in McAdam ellipses**: ≤6 Colour rendering index: 80 Service life [h]: 25000 Number of on/off cycles: ≥ 15000 Lighting angle [°]: 120 Luminous efficiency of the lamp [lm/W]: 104 Ambient temperature range to which the product can be exposed: 5÷25 Enclosure material: plastic Connection type: Free cable ends Wire length [m]: 0.1 Lamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤0,5 IP class: 44/20





Downlight fitting

LOGISTIC DATA: Packaging method: 1		
ACCES	SORIES:	
36520	TAVO FRAME DO 12W	Ramka do montażu natynkowego downlightów Kanlux TAVO LED.
A. S.	8. 8.	
36521	TAVO FRAME DO 18W	Ramka do montażu natynkowego downlightów Kanlux TAVO LED.
36522	TAVO FRAME DL 12W	Ramka do montażu natynkowego downlightów Kanlux TAVO LED.
36523	TAVO FRAME DL 18W	Ramka do montażu natynkowego downlightów Kanlux TAVO LED.
		Kanlux TAVO LED.

