


Downlight fitting 5905339365132















Kanlux TAVO LED is a family of flush-mounted downlights. They are available in two shapes (round and square) and 5 wattages - from 5W to 24W. Kanlux TAVO LED downlights are characterised by a minimalist, Scandinavian design. Additional advantages are their IP44/20 tightness, as well as the possibility of surface mounting the 12W and 18W models in the Kanlux TAVO FRAME.

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating

material: yes Height [mm]: 26 Diameter [mm]: 170

Assembly hole [mm]: Ø145

Mercury content in the lamp [mg]: 0 Integrated LED light source: yes Photobiological safety: RG0

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 18

Class of protection against electric shock: ||

Lampshade material: plastic Enclosure material: plastic Diode type: LED SMD Luminous flux [Im]: 1900

Useful luminous flux of the light source Φ use [lm] : 2610 Useful luminous flux of the light source Φ use [lm] : in sphere

(360°)

Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: 6


Colour rendering index: 80 Service life [h]: 25000

Date of issue: 27.02.2025, 13:43





Downlight fitting



Number of on/off cycles: ≥15000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 106

Ambient temperature range to which the product can be

exposed: 5÷25

Connection type: Free cable ends

Wire length [m]: 0.1 IP class: 44/20 Kształt: round

LOGISTIC DATA:


Unit of measurement: unit Packaging method: 60

Number of units in the secondary packaging: 1

Number of units in the packaging: 60


Net unit weight [g]: 142
Grammage [g]: 219.83
Gross unit weight [g]: 208
Length of a unit pack [cm]: 3.7
Width of a unit pack [cm]: 17.6
Height of a unit pack [cm]: 17.6

Weight of a cardboard box [kg]: 13.1898
Width of a cardboard box [cm]: 39
Height of a cardboard box [cm]: 38
Length of a cardboard box [cm]: 55
Volume of a cardboard box [m³]: 0.08151





Downlight fitting



C90 - C270



Downlight fitting

ACCESSORIES

36520

TAVO FRAME DO 12W

Ramka do montażu natynkowego downlightów Kanlux TAVO LED.



36521

TAVO FRAME DO 18W

Ramka do montażu natynkowego downlightów Kanlux

TAVO LED.



36522

TAVO FRAME DL 12W

Ramka do montażu

natynkowego downlightów Kanlux TAVO LED.



36523

TAVO FRAME DL 18W

Ramka do montażu natynkowego

downlightów Kanlux TAVO LED.



Date of issue: 27.02.2025, 13:43