

## 36516 TAVO LED DL 9W-NW


Downlight fitting

5905339365163

IP  
44/20



95x95



Kanlux TAVO LED is a family of flush-mounted downlights. They are available in two shapes (round and square) and 5 wattages - from 5W to 24W. Kanlux TAVO LED downlights are characterised by a minimalist, Scandinavian design. Additional advantages are their IP44/20 tightness, as well as the possibility of surface mounting the 12W and 18W models in the Kanlux TAVO FRAME.

### GENERAL DATA:

**Colour:** white

**Place of assembly:** Recessed mount in the ceiling

**Place of application:** Indoors

**Minimum distance from the illuminated object:** 0,5m

**Compatible with a dimmer:** no

**The product is not suitable to be covered with a heat-insulating material:** yes

**Length [mm]:** 120

**Width [mm]:** 120

**Height [mm]:** 26

**Assembly hole [mm]:** 95x95

**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 9

**Class of protection against electric shock:** II

**Lampshade material:** plastic

**Diode type:** LED SMD

**Luminous flux [lm]:** 900

**Colour temperature:** white

**Correlated colour temperature [K]:** 4000

**Colour consistency in McAdam ellipses:** ≤6

**Colour rendering index:** 80

**Service life [h]:** 25000

**Number of on/off cycles:** ≥15000

**Lighting angle [°]:** 120

**Luminous efficiency of the lamp [lm/W]:** 100

**Ambient temperature range to which the product can be exposed:** 5÷25

**Enclosure material:** plastic

**Connection type:** Free cable ends

**Wire length [m]:** 0.1

**Lamp-heating time [s]:** ≤1

**Lamp-ignition time [s]:** ≤0,5

**IP class:** 44/20

### Downlight fitting

#### LOGISTIC DATA:


Packaging method: 1

#### ACCESSORIES:

**36520** TAVO FRAME DO 12W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.



**36521** TAVO FRAME DO 18W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.



**36522** TAVO FRAME DL 12W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.



**36523** TAVO FRAME DL 18W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.

