

## **37114** HR-LH-WW-W-RM

# Linear LED luminaire 5905339371140






















HIERRO is a family of fixtures produced at the Kanlux Factory. The minimalist and elegant form fits into the latest trends in architectural design. The stylish solution is widely used in modern offices, shops, and loft spaces as basic, complementary or accent lighting. The great advantages of HIERRO luminaires are: variety of available control and installation methods, low UGR coefficient, high luminous efficiency, ability to adapt to specific lighting projects and 5-year warranty. This allows you to create energy-saving and modern lighting systems that provide attractive lighting effects.

#### **GENERAL DATA:**

Colour: white

Place of assembly: rail
Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no Fixture lighting direction: down

Length [mm]: 850 Width [mm]: 43 Height [mm]: 89

Integrated LED light source: yes

#### **TECHNICAL DATA:**

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 42

Class of protection against electric shock: II

Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 4950

Colour temperature: Warm white

Correlated colour temperature [K]: 3000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :

L90B10

Number of on/off cycles: ≥30000 Lighting angle [°]: X60/Y60

Luminous efficiency of the lamp [lm/W]: 118

Ambient temperature range to which the product can be

exposed: 5÷25

Shade type: louvre / white

Date of issue: 20.02.2024, 20:24






# **37114** HR-LH-WW-W-RM

## Linear LED luminaire





Enclosure material: steel, plastic

**IP class**: 20 **UGR**: <17

### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1140 Grammage [g]: 1560

Weight of a cardboard box [kg]: 1.56

KANLUX S.A. (kat 37114) HR-LH-WW-W-RM / Krzywa rozsyłu światła (biegunowo)

