



37279 BLINGO IP65 40W 60NW

Recessed-mounted LED panel

5905339372796



Kanlux BLINGO LED v2 are backlight panels. They are equipped with a junction box with a quick connector, which allows for pass-through connection of panels and speeds up their installation. In the new models of the well-known Kanlux BLINGO LED v2 panels, we have introduced an integrated power supply, thanks to which we can place them in an appropriate Kanlux ADTR frame and perform surface-mounting of the panels. BLINGO LED v2 panels have a grooved frame and higher luminous efficiency than their previous versions (Kanlux BLINGO LED).

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object : 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

Feeder included: yes

Length [mm]: 595

Width [mm]: 595

Height [mm]: 34

Mercury content in the lamp [mg] : 0

Integrated LED light source : yes

Number of modules (LED light source): 6

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 40

Class of protection against electric shock : II

Lampshade material: plastic

Enclosure material: steel

Panel/frame material: steel

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 4800

Useful luminous flux of the light source Φ_{use} [lm] : 960

Useful luminous flux of the light source Φ_{use} [lm] : in sphere (360°)

37279 BLINGO IP65 40W 60NW

Recessed-mounted LED panel

		BLINGO 24W 4320 60NW	BLINGO U24W 4000 60NW	BLINGO 34W 4080 60NW	BLINGO 34W 3740 60WW	BLINGO 34W 4080 60CW	BLINGO U34W 4080 60NW	BLINGO 34W 4080 120NW
	INDEX	37178	37179	37171	37170	37172	37173	37174
SPN PANEL 120	37336							✓
SPN PANEL 60-62	37335	✓	✓	✓	✓	✓	✓	
CLIPS PANEL 120	37338							✓
CLIPS PANEL 60-62	37337	✓	✓	✓	✓	✓	✓	
ADTR 6060 B	27615	✓	✓	✓	✓	✓	✓	
ADTR 6060 SR	27610	✓	✓	✓	✓	✓	✓	
ADTR 6060 W	27613	✓	✓	✓	✓	✓	✓	
ADTR-S 6060 W	27616	✓	✓	✓	✓	✓	✓	
ADTR 12030 B	27614							✓
ADTR 12030 SR	27612							✓
ADTR 12030 W	27611							✓
ADTR-H 6060 B	29845	✓	✓	✓	✓	✓	✓	
ADTR-H 6060 SR	29844	✓	✓	✓	✓	✓	✓	
ADTR-H 6060 W	29843	✓	✓	✓	✓	✓	✓	
ADTR-S-H 6060 W	27617	✓	✓	✓	✓	✓	✓	
ADTR-H 76MM 6060 W	33398	✓	✓	✓	✓	✓	✓	
ADTR-H 12030 B	33391							✓
ADTR-H 12030 SR	33392							✓
ADTR-H 12030 W	33390							✓
ADTR-H 6262 W	33435							

		BLINGO 38W 4560 60NW	BLINGO 38W 4560 120NW	BLINGO TN38W 6060 NW	BLINGO TUN48W 6060 NW	BLINGO IPR38W 6060NW	BLINGO IP65 40W 60NW
	INDEX	37176	37177	33177	33179	33174	37279
SPN PANEL 120	37336		✓				
SPN PANEL 60-62	37335	✓		✓	✓	✓	✓
CLIPS PANEL 120	37338		✓				
CLIPS PANEL 60-62	37337	✓		✓	✓	✓	✓
ADTR 6060 B	27615	✓		✓	✓		
ADTR 6060 SR	27610	✓		✓	✓		
ADTR 6060 W	27613	✓		✓	✓		
ADTR-S 6060 W	27616	✓		✓	✓		
ADTR 12030 B	27614		✓				
ADTR 12030 SR	27612		✓				
ADTR 12030 W	27611		✓				
ADTR-H 6060 B	29845	✓		✓	✓	✓	✓
ADTR-H 6060 SR	29844	✓		✓	✓	✓	✓
ADTR-H 6060 W	29843	✓		✓	✓	✓	✓
ADTR-S-H 6060 W	27617	✓		✓	✓	✓	✓
ADTR-H 76MM 6060 W	33398	✓		✓	✓	✓	✓
ADTR-H 12030 B	33391		✓				
ADTR-H 12030 SR	33392		✓				
ADTR-H 12030 W	33390		✓				
ADTR-H 6262 W	33435						

Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses : 6
Colour rendering index: 90
Service life [h]: 50000
Luminous-flux-retention factor at the end of rated service life : L70B50
Number of on/off cycles : ≥25000
Lighting angle [°]: 120
Luminous efficiency of the lamp [lm/W]: 120
Ambient temperature range to which the product can be exposed: 5÷25
Range of sections of wires used [mm²]: 1-2,5
IP class: 65
Kształt: square
UGR: <22

LOGISTIC DATA:


Unit of measurement: unit
Packaging method: 5
Number of units in the secondary packaging : 1
Number of units in the packaging : 5
Net unit weight [g]: 1520
Grammage [g]: 2132
Length of a unit pack [cm]: 60.5
Width of a unit pack [cm]: 4
Height of a unit pack [cm]: 60.5
Weight of a cardboard box [kg]: 10.66
Width of a cardboard box [cm]: 22
Height of a cardboard box [cm]: 63
Length of a cardboard box [cm] : 63
Volume of a cardboard box [m³]: 0.087318

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

37279 BLINGO IP65 40W 60NW

Recessed-mounted LED panel



KANLUX S.A. (kat 37279) BLINGO IP65 40W NW / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 37279) BLINGO IP65 40W NW
Lampy: 6 x BLINGO IP65 40W NW

