



37281 KMCCB-RT-125A

Wyłącznik kompaktowy MCCB

5905339372819



GENERAL DATA:

Utilisation category: A

Place of assembly: mounting plate

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 125

Rated frequency [Hz]: 50

Connection type: Terminal block

Control type: mechaniczne

Rated breaking voltage Ue [V]: 380/415; 220/230

IP class: 20

Rated insulation voltage UI [V]: 800

Rated impulse withstand voltage Uimp [V]: 8000

Number of poles: 3

Znamionowa graniczna zwarciova zdolność łączeniowa Icu :

25kA (380/415V AC); 36kA (220/230V AC)

Prąd znamionowy wyłączalny zwarciovy roboczy Ics : 18kA

(380/415V AC); 25kA (220/230V AC)

Zakres regulacji członu termicznego: regulowane

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 20

Number of units in the secondary packaging : 1

Number of units in the packaging : 20

Net unit weight [g]: 896

Grammage [g]: 968.5

Gross unit weight [g]: 942

Length of a unit pack [cm]: 14

Width of a unit pack [cm]: 8.5

Height of a unit pack [cm]: 9

Weight of a cardboard box [kg]: 19.37

Width of a cardboard box [cm]: 30

Height of a cardboard box [cm]: 20.5

Length of a cardboard box [cm]: 44.5

Volume of a cardboard box [m³]: 0.027368