


37282 KMCCB-RT-160A

Wyłącznik kompaktowy MCCB

5905339372826



GENERAL DATA:

Utilisation category: A

Place of assembly: mounting plate

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 160

Rated frequency [Hz]: 50

Connection type: Terminal block

Control type: mechaniczne

Rated breaking voltage Ue [V]: 380/415; 220/230

IP class: 20

Rated insulation voltage UI [V]: 800

Rated impulse withstand voltage Uimp [V]: 8000

Number of poles: 3

Znamionowa graniczna zwarciova zdolność łączeniowa Icu :

36kA (380/415V AC); 50kA (220/230V AC)

Prąd znamionowy wyłączalny zwarciovy roboczy Ics : 27kA

(380/415V AC); 36kA (220/230V AC)

Zakres regulacji członu termicznego: regulowane

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 12

Number of units in the secondary packaging : 1

Number of units in the packaging: 12

Net unit weight [g]: 1642

Grammage [g]: 1761.67

Gross unit weight [g]: 1712

Length of a unit pack [cm]: 17.5

Width of a unit pack [cm]: 12

Height of a unit pack [cm]: 11

Weight of a cardboard box [kg]: 21.14004

Width of a cardboard box [cm]: 36.5

Height of a cardboard box [cm]: 24

Length of a cardboard box [cm]: 37

Volume of a cardboard box [m³]: 0.032412