


## 37284 KMCCB-RT-250A

Wyłącznik kompaktowy MCCB

5905339372840



### GENERAL DATA:

Utilisation category: A

Place of assembly: mounting plate

### TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 250

Rated frequency [Hz]: 50

Connection type: Terminal block

Control type: mechaniczne

Rated breaking voltage  $U_e$  [V]: 380/415; 220/230

IP class: 20

Rated insulation voltage  $U_i$  [V]: 800

Rated impulse withstand voltage  $U_{imp}$  [V]: 8000

Number of poles: 3

Znamionowa graniczna zwarciova zdolność łączeniowa  $I_{cu}$  :  
36kA (380/415V AC); 50kA (220/230V AC)

Prąd znamionowy wyłączalny zwarciovy roboczy  $I_{cs}$  : 27kA  
(380/415V AC); 36kA (220/230V AC)

Zakres regulacji członu termicznego: regulowane

### LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 12

Number of units in the secondary packaging : 1

Number of units in the packaging : 12

Net unit weight [g]: 1718

Grammage [g]: 1773.33

Gross unit weight [g]: 1788

Length of a unit pack [cm]: 17.5

Width of a unit pack [cm]: 12

Height of a unit pack [cm]: 11

Weight of a cardboard box [kg]: 21.27996

Width of a cardboard box [cm]: 36.5

Height of a cardboard box [cm]: 24

Length of a cardboard box [cm]: 37

Volume of a cardboard box [m<sup>3</sup>]: 0.032412