


PIR motion sensor

5905339373632



The latest model of an infrared motion sensor in the ALER family. A maximum detection range of 12m and a high IP65 rating make it a versatile solution for many applications. Available in two colors, wall-mounted installation.

GENERAL DATA:

Colour: black
Place of assembly: wall mounted
Place of application: Indoors and outdoors
Micro-interval between relay contacts: yes
Length [mm]: 120
Width [mm]: 80
Height [mm]: 52

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Class of protection against electric shock : II
Material: plastic
Ambient temperature range to which the product can be exposed: -20÷40
Sensor type: PIR
Connection type: Bolt terminal block
Range of sections of wires used [mm²]: 0,75÷1,5
Sensor-operation time [second-minute]: 10-15
sensor working angle [°]: 120
Maximum operating time [min]: 15
Minimum operating time[s]: 10
Maximum power [VA]: 1200
Illumination-level setpoint by which the sensor detects movement [lx]: 3-2000
IP class: 65
Sensor range[m]: max 12

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 50
Number of units in the secondary packaging : 1
Number of units in the packaging: 50
Net unit weight [g]: 162
Grammage [g]: 212.8
Length of a unit pack [cm]: 8.5
Width of a unit pack [cm]: 7

PIR motion sensor

Height of a unit pack [cm]: 10.5

Weight of a cardboard box [kg]: 10.64

Width of a cardboard box [cm]: 40.5

Height of a cardboard box [cm]: 24

Length of a cardboard box [cm] : 44

Volume of a cardboard box [m³]: 0.042768