

37366 SENTO-O-WT-W

PIR motion sensor 5905339373663

















Kanlux SENTO-O is an electronic sensor for movement detection. Its exceptionality lies in the fact that as many as three infrared detectors are installed in one sensor. This guarantees an unprecedented sensitivity and allows you to capture even the slightest movement. Kanlux SENTO, due to its unique features, is referred to as presence sensors. The additional advantage is universal installation - flush-mounted and surface-mounted.

GENERAL DATA:

Colour: white

Place of assembly: ceiling mounted, Recessed mount in the

ceiling

Place of application: Indoors and outdoors **Micro-interval between relay contacts**: yes

Height MAX [mm]: 74 Diameter [mm]: 111 Assembly hole [mm]: Ø66

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50

Class of protection against electric shock: ||

Material: plastic

Ambient temperature range to which the product can be

exposed: -20÷40 Sensor type: 3xPIR

Connection type: Terminal block

Range of sections of wires used [mm²]: 0,75÷1,5 Sensor-operation time [second-minute]: 10-30

sensor working angle [°]: H360

Maximum operating time [min]: 30

Minimum operating time[s]: 10

Maximum power [VA]: 2000

Illumination-level setpoint by which the sensor detects

movement [lx]: 3-2000

IP class: 44/20

Sensor range[m]: max 20


Date of issue: 04.02.2025, 10:53





37366 SENTO-O-WT-W

PIR motion sensor





LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 180
Grammage [g]: 256.8
Gross unit weight [g]: 240
Length of a unit pack [cm]: 11.5
Width of a unit pack [cm]: 8.5
Height of a unit pack [cm]: 12

Weight of a cardboard box [kg]: 12.84
Width of a cardboard box [cm]: 48
Height of a cardboard box [cm]: 26
Length of a cardboard box [cm]: 60
Volume of a cardboard box [m³]: 0.07488