37464 KND-S6D-WW-W-P1

Recessed - Mounted LED Office Fixture 5905339374646
















KND W P1







GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: DALI

The product is not suitable to be covered with a heat-insulating

material: yes Length [mm]: 595 Width [mm]: 595 Height [mm]: 39

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 20

Class of protection against electric shock: I

Lampshade material: plastic Diode type: LED SMD

Luminous flux of the light fitting [lm]: 2800

Colour temperature: Warm white

Correlated colour temperature [K]: 3000 Colour consistency in McAdam ellipses: 6

Colour rendering index: 80 Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :

L90B10

Number of on/off cycles: ≥30000

Lighting angle [°]: 60

Luminous efficiency of the lamp [lm/W]: 140

Ambient temperature range to which the product can be

exposed: 5÷25

Shade type: soczewka Enclosure material: Metal

Connection type: Self-clamping block

Range of sections of wires used [mm²]: $0.5 \div 2.5$

IP class: 20

LOGISTIC DATA:


Unit of measurement: unit Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 2280








37464 KND-S6D-WW-W-P1

Recessed - Mounted LED Office Fixture



Grammage [g]: 2340

Gross unit weight [g]: 2340 Length of a unit pack [cm]: 63 Width of a unit pack [cm]: 61 Height of a unit pack [cm]: 5.5 Weight of a cardboard box [kg]

Weight of a cardboard box [kg]: 2.34 Width of a cardboard box [cm]: 61 Height of a cardboard box [cm]: 5.5 Length of a cardboard box [cm]: 63

Volume of a cardboard box [m³]: 0.021137



