

Recessed - Mounted LED Office Fixture

5905339375162



GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object : 0,5m

Compatible with a dimmer: DALI

The product is not suitable to be covered with a heat-insulating material: yes

Length [mm]: 1195

Width [mm]: 295

Height [mm]: 39

Integrated LED light source : yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 26

Class of protection against electric shock : I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 4050

Colour temperature: Warm white

Correlated colour temperature [K]: 3000

Colour consistency in McAdam ellipses : 6

Colour rendering index: 80

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :
L90B10

Number of on/off cycles: ≥ 30000

Lighting angle [°]: 90

Luminous efficiency of the lamp [lm/W]: 156

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: soczewka

Enclosure material: Metal

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5÷2,5

IP class: 20

LOGISTIC DATA:


Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging : 1

37516 KND-L9D-WW-W-P3

Recessed - Mounted LED Office Fixture



Number of units in the packaging : 1

Net unit weight [g] : 2700

Grammage [g] : 2780

Gross unit weight [g] : 2780

Length of a unit pack [cm] : 123

Width of a unit pack [cm] : 32.5

Height of a unit pack [cm] : 5.5

Weight of a cardboard box [kg] : 2.78

Width of a cardboard box [cm] : 32.5

Height of a cardboard box [cm] : 5.5

Length of a cardboard box [cm] : 123

Volume of a cardboard box [m³] : 0.021986

