

38143 MAH PRO Y 52W 15R-NW

LED dustproof lighting fitting

5905339381439



up to
170 lm
W

IP
65



Kanlux MAH PRO 7Y luminaires are the latest series of hermetic luminaires, characterized by an opening housing, designed with the highest quality and functionality in mind. Equipped with branded components, including the TRIDONIC power supply and Everlight LEDs, they enable a warranty of up to 7 years. These fixtures are synonymous with reliability. With a luminous efficiency of up to 170lm/W and an IP65 parameter, they provide excellent lighting in all conditions. Additionally, thanks to the ability to adjust the power and light flux, as well as the option of replacing the power supply and adding a motion sensor, they are extremely versatile in their use. Easy installation via quick connectors and through wiring makes installation quick and hassle-free. An additional advantage is high protection against mechanical damage IK08. This is an irreplaceable series for those who require excellent quality and reliability in all conditions.

GENERAL DATA:

Colour: grey

Place of assembly: ceiling mounted, wall mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Possibility of fixture-loop-through connection: yes

Compatible with a dimmer: no

Length [mm]: 1500

Width [mm]: 75

Height [mm]: 75

Number of chokes: 2

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 52 / 44,5 / 37 / 29,5

Class of protection against electric shock: I

Lampshade material: PC

Diode type: LED SMD

Luminous flux [lm]: 8400 / 7300 / 6200 / 5000

Colour temperature: white


Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: 6

Colour rendering index: 80


Service life [h]: 100000

Number of on/off cycles: ≥80000



38143 MAH PRO Y 52W 15R-NW

LED dustproof lighting fitting



Lighting angle [°]: 110

Ambient temperature range to which the product can be exposed: -20÷40

Enclosure material: PC

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1÷2,5

IK class: 08

IP class: 65

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 9

Number of units in the secondary packaging: 1

Number of units in the packaging: 9

Net unit weight [g]: 1688

Grammage [g]: 1955.56

Gross unit weight [g]: 1860

Length of a unit pack [cm]: 150.5

Width of a unit pack [cm]: 8

Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 17.60004

Width of a cardboard box [cm]: 27


Height of a cardboard box [cm]: 26

Length of a cardboard box [cm]: 151.5

Volume of a cardboard box [m³]: 0.106353

ADDITIONAL INFORMATION:

- 7 years Warranty under the terms of the warranty statement, available on our website




38143 MAH PRO Y 52W 15R-NW

LED dustproof lighting fitting

KANLUX S.A. (kat 38143) MAH PRO Y 52W 15R-NW / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 38143) MAH PRO Y 52W 15R-NW
Lampy: 1 x MAH PRO 52W 15R - 8400lm



ACCESSORIES

38144

MAH PRO SENSOR Czujnik ruchu - (38144)
MAH PRO SENSOR

