


03844 DB118F 1X18P/FMD

DB-series distribution board

5905339038449











DB series switchboards, meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections.

GENERAL DATA:

Colour: white / grey Door colour: grey

Place of assembly: Recessed mount in the wall

Norm: PN-EN 62208

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 63 Rated frequency [Hz]: 50

Class of protection against electric shock: ||

Material: plastic

Number of modules: 18P

Temperature resistance [°C]: 650

IK class: 06 IP class: 40

number of rows: 1

LOGISTIC DATA:

Packaging method: 10


Number of units in the secondary packaging: 1

Number of units in the packaging: 10

Net unit weight [g]: 1002 Grammage [g]: 1290

Length of a unit pack [cm]: 40 Width of a unit pack [cm]: 26 Height of a unit pack [cm]: 11

Weight of a cardboard box [kg]: 12.9 Width of a cardboard box [cm]: 42 Height of a cardboard box [cm]: 53 Length of a cardboard box [cm]: 58 Volume of a cardboard box [m³]: 0.129108



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





03844 DB118F 1X18P/FMD

DB-series distribution board

