


## **38538** KRD10-2/63/300-B

Residual-current circuit breaker, 2P 5905339385383







#### **GENERAL DATA:**

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61008-1 Length [mm]: 73 Width [mm]: 54 Height [mm]: 86.7

### TECHNICAL DATA:

Rated voltage [V]: 230 AC Rated current [A]: 63 Rated frequency [Hz]: 50

Ambient temperature range to which the product can be

exposed: -25÷40

Range of sections of wires used [mm<sup>2</sup>]: do 35

Residual-current protection type: B

Number of modules: 3

Differential-rated current [mA]: 300

IP class: 20

Rated activation capacity[A]: 10000 Rated insulation voltage UI [V]: 400

Number of poles: 2

### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 3

Number of units in the secondary packaging: 3

Number of units in the packaging: 30

Net unit weight [g]: 424 Grammage [g]: 483.33 Gross unit weight [g]: 444 Length of a unit pack [cm]: 8 Width of a unit pack [cm]: 9 Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 14.4999 Width of a cardboard box [cm]: 27

Height of a cardboard box [cm]: 19 Length of a cardboard box [cm]: 49.5





# 38538 KRD10-2/63/300-B

Residual-current circuit breaker, 2P

Volume of a cardboard box [m³]: 0.025394

