


38729 KRD10-2/40/30-AC

Residual-current circuit breaker, 2P

5905339387295



Differential circuit breaker: is used for additional protection against electric shock, designed to operate in circuits of sinusoidal alternating current (AC type) and sinusoidal alternating and pulsating current with a constant component (type A).

GENERAL DATA:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61008-1

Length [mm]: 75

Width [mm]: 36

Height [mm]: 81

TECHNICAL DATA:

Rated voltage [V]: 230 AC

Rated current [A]: 40

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: max 25

Residual-current protection type: AC

Number of modules: 2

Differential-rated current [mA]: 30

IP class: 20

Rated activation capacity[A]: 10000

Rated insulation voltage UI [V]: 400

Number of poles: 2

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 60

Number of units in the secondary packaging : 1

Number of units in the packaging : 60

Net unit weight [g]: 208

Grammage [g]: 235.83

Gross unit weight [g]: 228

Length of a unit pack [cm]: 9

38729 KRD10-2/40/30-AC

Residual-current circuit breaker, 2P

Width of a unit pack [cm] : 4
Height of a unit pack [cm] : 8
Weight of a cardboard box [kg] : 14.1498
Width of a cardboard box [cm] : 27.5
Height of a cardboard box [cm] : 18.5
Length of a cardboard box [cm] : 47
Volume of a cardboard box [m³] : 0.023911