


38738 KRD10-4/25/30-A

Residual-current circuit breaker, 4P

5905339387387



Differential circuit breaker: is used for additional protection against electric shock, designed to operate in circuits of sinusoidal alternating current (AC type) and sinusoidal alternating and pulsating current with a constant component (type A).

GENERAL DATA:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61008-1

Length [mm]: 75

Width [mm]: 72

Height [mm]: 82

TECHNICAL DATA:

Rated voltage [V]: 400 AC

Rated current [A]: 25

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: max 25

Residual-current protection type: A

Number of modules: 4

Differential-rated current [mA]: 30

IP class: 20

Rated activation capacity[A]: 10000

Rated insulation voltage UI [V]: 400

Number of poles: 4

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 30

Number of units in the secondary packaging : 1

Number of units in the packaging : 30

Net unit weight [g]: 340

Grammage [g]: 384.67

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 8

38738 KRD10-4/25/30-A

Residual-current circuit breaker, 4P

Height of a unit pack [cm]: 8
Weight of a cardboard box [kg]: 11.5401
Width of a cardboard box [cm]: 27.5
Height of a cardboard box [cm]: 18
Length of a cardboard box [cm]: 47
Volume of a cardboard box [m³]: 0.023265