

## 39110 SOLN LED CCTDIM W/G

Ceiling-mounted LED light fitting

5905339391100



**1800K**  
SUPER  
WARM



Kanlux SOLN LED CCT DIM are elegant ceiling lamps that combine functionality with decorative appeal. Equipped with adjustable light color (2700K, 4000K, 6500K) and a dimming function, they allow you to tailor the lighting to your mood and needs. With a luminous flux of up to 1460lm, the fixtures guarantee comfortable lighting in both bedrooms and living rooms. An additional advantage is the Night Light mode, providing a gentle night light with a color temperature of 3000K, and the Sunset Light mode, which brings a soft, warm light inspired by the sunset. This function helps you unwind after a busy day, creating an atmosphere conducive to rest, relaxation, or evening reading. The fixture has a 380mm diameter and subtle color finishes (white, black, gold), making the SOLN LED a practical and stylish light source.

### GENERAL DATA:

**Colour:** white / gold

**Place of assembly:** ceiling mounted

**Place of application:** Indoors

**Minimum distance from the illuminated object:** 0,5m

**Built-in brightness control:** yes

**Compatible with a dimmer:** no

**Control:** infrared remote control

**Height [mm]:** 75

**Diameter [mm]:** 380

**Mercury content:** no

**Integrated LED light source:** yes

**Number of modules (LED light source):** 4

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** max 25

**Class of protection against electric shock:** I

**Lampshade material:** plastic

**Enclosure material:** Metal

**Light source:** LED


**Diode type:** LED SMD

**Night Light function:** 13W / 460lm / 2700K

**Luminous flux [lm]:** max 1460 (4000K)

## 39110 SOLN LED CCTDIM W/G

Ceiling-mounted LED light fitting



**Useful luminous flux of the light source  $\Phi_{use}$  [lm]** : 600  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]** : in sphere (360°)  
**Colour temperature:** Warm white, white, cold white  
**Correlated colour temperature [K]** : 2700-6500  
**Colour consistency in McAdam ellipses** : 6  
**Colour rendering index** : 90  
**Service life [h]** : 20000  
**Number of on/off cycles** :  $\geq 20000$   
**Lighting angle [°]** : 120  
**Ambient temperature range to which the product can be exposed** : 5÷25  
**Connection type:** Bolt terminal block  
**Range of sections of wires used [mm<sup>2</sup>]** : 1,5  
**IP class** : 20  
**Kształt** : round

### LOGISTIC DATA:

**Unit of measurement:** unit  
**Packaging method:** 10  
**Number of units in the secondary packaging** : 1  
**Number of units in the packaging** : 10  
**Net unit weight [g]** : 864  
**Grammage [g]** : 1252  
**Length of a unit pack [cm]** : 42  
**Width of a unit pack [cm]** : 8.5  
**Height of a unit pack [cm]** : 42  
**Weight of a cardboard box [kg]** : 12.52  
**Width of a cardboard box [cm]** : 45  
**Height of a cardboard box [cm]** : 45  
**Length of a cardboard box [cm]** : 85  
**Volume of a cardboard box [m<sup>3</sup>]** : 0.172125