

39111 SOLN LED CCTDIM B/G

Ceiling-mounted LED light fitting

5905339391117



1800K
SUPER
WARM



Kanlux SOLN LED CCT DIM are elegant ceiling lamps that combine functionality with decorative appeal. Equipped with adjustable light color (2700K, 4000K, 6500K) and a dimming function, they allow you to tailor the lighting to your mood and needs. With a luminous flux of up to 1460lm, the fixtures guarantee comfortable lighting in both bedrooms and living rooms. An additional advantage is the Night Light mode, providing a gentle night light with a color temperature of 3000K, and the Sunset Light mode, which brings a soft, warm light inspired by the sunset. This function helps you unwind after a busy day, creating an atmosphere conducive to rest, relaxation, or evening reading. The fixture has a 380mm diameter and subtle color finishes (white, black, gold), making the SOLN LED a practical and stylish light source.

GENERAL DATA:


Colour: black/gold
Place of assembly: ceiling mounted
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Built-in brightness control: yes
Compatible with a dimmer: no
Control: infrared remote control
Height [mm]: 75
Diameter [mm]: 380
Mercury content: no
Integrated LED light source: yes
Number of modules (LED light source): 4

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: max 25
Class of protection against electric shock: I
Lampshade material: plastic
Enclosure material: Metal
Light source: LED
Diode type: LED SMD
Night Light function: 13W / 460lm / 2700K
Luminous flux [lm]: max 1460 (4000K)

39111 SOLN LED CCTDIM B/G

Ceiling-mounted LED light fitting



Useful luminous flux of the light source Φ_{use} [lm] : 600
Useful luminous flux of the light source Φ_{use} [lm] : in sphere (360°)
Colour temperature: Warm white, white, cold white
Correlated colour temperature [K] : 2700-6500
Colour consistency in McAdam ellipses : 6
Colour rendering index : 90
Service life [h] : 20000
Number of on/off cycles : ≥ 20000
Lighting angle [°] : 120
Ambient temperature range to which the product can be exposed : 5÷25
Connection type: Bolt terminal block
Range of sections of wires used [mm²] : 1,5
IP class : 20
Kształt : round

LOGISTIC DATA:

Unit of measurement: unit
Packaging method : 10
Number of units in the secondary packaging : 1
Number of units in the packaging : 10
Net unit weight [g] : 864
Grammage [g] : 1252
Length of a unit pack [cm] : 42
Width of a unit pack [cm] : 8.5
Height of a unit pack [cm] : 42
Weight of a cardboard box [kg] : 12.52
Width of a cardboard box [cm] : 45
Height of a cardboard box [cm] : 45
Length of a cardboard box [cm] : 85
Volume of a cardboard box [m³] : 0.172125