

39240 BLINGO UIP 125LM120NW

Flush-mounted LED panel without power supply included

5905339392404



low
UGR

IP
54



GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Feeder included: no

Driver [index]: 37272 (600mA); 37269 (850mA); 37270 (1100mA)

Length [mm]: 1195

Width [mm]: 295

Height [mm]: 26

Mercury content in the lamp [mg]: 0

Integrated LED light source: yes

Number of modules (LED light source): 3

TECHNICAL DATA:

Power-supply current [mA]: 600/850/1100

Maximum power [W]: max 40

Class of protection against electric shock: III

Lampshade material: plastic

Enclosure material: steel

Panel/frame material: steel

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 3000 (600mA); 4000 (850mA); 5000 (1100mA)

Luminous efficiency [lm/W]: max 125

Useful luminous flux of the light source Φ_{use} [lm]: 2020

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: 6

Colour rendering index: 90

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L70B50

Number of on/off cycles: ≥ 50000

Lighting angle [°]: 90


Ambient temperature range to which the product can be exposed: 5÷25

Shade type: microprismatic



39240 BLINGO UIP 125LM120NW

Flush-mounted LED panel without power supply included



Connection type: przewód zakończony wtyczką - DC

Power-supply type: direct current

IP class: 54/20

Kształt: rectangular

UGR: <19

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1604

Grammage [g]: 2090

Gross unit weight [g]: 1908

Length of a unit pack [cm]: 120.5

Width of a unit pack [cm]: 30

Height of a unit pack [cm]: 3.5

Weight of a cardboard box [kg]: 10.45

Width of a cardboard box [cm]: 19.5

Height of a cardboard box [cm]: 32

Length of a cardboard box [cm]: 122

Volume of a cardboard box [m³]: 0.076128

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

ACCESSORIES

37272

BLINGO DRV 24W ON-OFF

Zasilacz LED dedykowany pod panel BLINGO U E125LM 30NW(37271), BLINGO UHRA 95 120NW (39171) BLINGO UHRA 95 60NW (39170), BLINGO UIP 125LM 60NW (39239), BLINGO UIP 125LM120NW (39240), BLINGO UIP 125LM 30NW (39238)



39240 BLINGO UIP 125LM120NW

Flush-mounted LED panel without power supply included

37269

BLINGO DRV 32W ON-OFF

Zasilacz LED dedykowany do paneli BLINGO U E125LM 120NW(37266), BLINGO U E125LM 60NW(37265), BLINGO UHRA 95 120NW (39171), BLINGO UHRA 95 60NW (39170), BLINGO UIP 125LM 60NW (39239), BLINGO UIP 125LM120NW (39240)



37270

BLINGO DRV 40W ON-OFF

Zasilacz LED dedykowany do paneli BLINGO U E125LM 120NW(37266), BLINGO U E125LM 60NW(37265), BLINGO UHRA 95 120NW (39171), BLINGO UHRA 95 60NW (39170), BLINGO UIP 125LM 60NW (39239), BLINGO UIP 125LM120NW (39240)



39240 BLINGO UIP 125LM120NW

Flush-mounted LED panel without power supply included

37268

BLINGO DRV40W1-10V BK



Zasilacz LED dedykowany do paneli BLINGO U E125LM 120NW (37266), BLINGO U E125LM 60NW (37265), BLINGO U E125LM 30NW (37271), BLINGO UHRA 95 120NW (39171), BLINGO UHRA 95 60NW (39170), BLINGO UIP 125LM 60NW (39239), BLINGO UIP 125LM120NW (39240), BLINGO UIP 125LM 30NW (39238)

37267

BLINGO DRV42W DALI BK



Zasilacz LED dedykowany do paneli BLINGO U E125LM 120NW (37266), BLINGO U E125LM 60NW (37265), BLINGO U E125LM 30NW (37271), BLINGO UHRA 95 120NW (39171), BLINGO UHRA 95 60NW (39170), BLINGO UIP 125LM 60NW (39239), BLINGO UIP 125LM120NW (39240), BLINGO UIP 125LM 30NW (39238)