


39327 KMB10-C63/4

Miniature circuit breaker, 4P

5905339393272



GENERAL DATA:

Place of assembly: na szynę TH35

Norm: PN-EN 60898-1

Length [mm]: 76

Width [mm]: 70

Height [mm]: 82

TECHNICAL DATA:

Rated voltage [V]: 400 AC

Rated current [A]: 63

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -5÷40

Range of sections of wires used [mm²]: 1÷25

Release characteristics: C

Energy-limit class: 3

Number of modules: 4

Rated short-circuit current [A]: 10000

IP class: 20

Rated insulation voltage UI [V]: 500

Number of poles: 4

Mechanical endurance: 10000

Electrical endurance: 4000

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 3

Number of units in the secondary packaging: 3

Number of units in the packaging: 30

Net unit weight [g]: 424

Grammage [g]: 459.33

Gross unit weight [g]: 456

Length of a unit pack [cm]: 7.2

Width of a unit pack [cm]: 7.2

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 13.7799

Width of a cardboard box [cm]: 25

Height of a cardboard box [cm]: 19

39327 KMB10-C63/4

Miniature circuit breaker, 4P

Length of a cardboard box [cm] : 46

Volume of a cardboard box [m³] : 0.02185