



00460 ALER JQ-30-W

PIR motion sensor 5905339004604









Kanlux ALER JQ is a motion detector whose maximum detection range comes to 12 metres. You can set adjustments of the lighting time and light intensity level at which the detector works.

GENERAL DATA:

Colour: white Place of assembly: wall mounted Place of application: Indoors and outdoors Micro-interval between relay contacts: yes Width [mm]: 97 Height [mm]: 75

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Class of protection against electric shock : II Material: plastic Ambient temperature range to which the product can be exposed: -20÷40 Sensor type: PIR Connection type: Bolt terminal block Range of sections of wires used [mm²]: 1+2,5 Sensor-operation time [second-minute]: 8-7 sensor working angle [°]: H160/V20 Maximum operating time [min]: 7 Minimum operating time[s]: 8 Maximum power [VA]: 1200 Illumination-level setpoint by which the sensor detects movement [lx]: 3-2000 IP class: 44 Sensor range[m]: max 12

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50 Number of units in the secondary packaging: 1 Number of units in the packaging: 50 Net unit weight [g]: 130 Grammage [g]: 193

Date of issue: 04.02.2025, 13:56

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample. Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com



00460 ALER JQ-30-W

PIR motion sensor

Gross unit weight [g]: 182 Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 9 Height of a unit pack [cm]: 10.5 Weight of a cardboard box [kg]: 9.65 Width of a cardboard box [cm]: 46 Height of a cardboard box [cm]: 24 Length of a cardboard box [cm]: 48 Volume of a cardboard box [m³]: 0.052992

ADDITIONAL INFORMATION:

- Maximum movement detection up to 12m
- Maximum horizontal angle of operation of the motion sensor $160^{\circ}\,$
- Light on time adjustable from 8s to 8min
- Capability to set the light intensity of the environment in which
 the device works

ACCESSORIES

26434

H-16MM2 PP M

M Złączka śrubowa, 12torowa, 16mm2