

70523 MILO 7040T/P

Bulkhead fixture 5905339705235






















Kanlux MILO is a classic channel luminaire used usually in technical rooms, garages, basements, staircases, corridors, etc. The luminaire has a metal (7040T) or plactic (7040T/P) protective mesh which protects the shade from mechanical damage.

GENERAL DATA:

Colour: grey

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes

Length [mm]: 165 Width [mm]: 100 Height [mm]: 110

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 25

Class of protection against electric shock: ||

Lampshade material: glass Enclosure material: plastic Light source: GLS/CFL/LED Light source included: no Cap (Light source): E27

Connection type: Terminal block

Range of sections of wires used [mm²]: 1-1,5

IK class: 06 IP class: 44

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 12

Number of units in the secondary packaging: 1

Number of units in the packaging: 12

Net unit weight [g]: 410 Grammage [g]: 441.67 Gross unit weight [g]: 458 Length of a unit pack [cm]: 18

Date of issue: 04.08.2025, 14:26



70523 MILO 7040T/P

Bulkhead fixture



Width of a unit pack [cm]: 13 Height of a unit pack [cm]: 12

Weight of a cardboard box [kg]: 5.30004
Width of a cardboard box [cm]: 18
Height of a cardboard box [cm]: 35
Length of a cardboard box [cm]: 48
Volume of a cardboard box [m³]: 0.03024

KANLUX S.A. (kat 70523) MILO 7040T P / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 70523) MILO 7040T P Lampy: 1 x A60 60W/c

