Kanlux

70524 HERMI 7063NB

Bulkhead fixture

5905339705242

CFL
LED/GLS
MADE IN POLAND
PROTECTIVE grid

CE EAC UKCA

Kanlux HERMI is a channel luminaire with a high tightness rating (IP54), which means high protection against dust and water splashes. The luminaire also has a metal mesh which protects the shade from mechanical damage.

GENERAL DATA:

Colour: white
Place of assembly: wall mounted, ceiling mounted
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,5m
Length [mm]: 190
Width [mm]: 110
Height [mm]: 124

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: max 100
Class of protection against electric shock: II
Lampshade material: glass
Light source: GLS/CFL/LED
Light source included: no
Cap: E27
Ambient temperature range to which the product can be exposed: -20÷25
Enclosure material: bakelite
Connection type: Terminal block
Range of sections of wires used [mm²]: 1-1,5
IP class: 54

LOGISTIC DATA:

Packaging method: 12
Number of units in the packaging: 12
Net unit weight [g]: 720
Grammage [g]: 750
Length of a unit pack [cm]: 19
Width of a unit pack [cm]: 13.5
Height of a unit pack [cm]: 13
Weight of a cardboard box [kg]: 9
Width of a cardboard box [cm]: 20
Height of a cardboard box [cm]: 38
Length of a cardboard box [cm] : 50
Volume of a cardboard box [m³]: 0.038

124
ø190

110
ø190

EN

Bulkhead fixture

KANLUX S.A. (kat 70524) HERMI 7063NB / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 70524) HERMI 7063NB
Lampy: 1 x A60 60W/c

cd/klm
C0 - C180   C90 - C270

EN