


70911 CYKLON EOL100B

Ducted fan

8594056490028



Kanlux CYKLON EOL series of fans is available in three sizes with diameter of 100, 120 and 150mm. They are made of plastic, in white colour. Their power is 19, 20 and 22W respectively. The number of rotations from each size comes to 2550/min.

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the wall

Place of application: Indoors

Length [mm]: 140

Width [mm]: 101

Height [mm]: 130

Assembly hole [mm]: Ø100

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 19

Class of protection against electric shock: II

Engine rotation: 2550

Bearing type: sliding

Connection type: Terminal block

Range of sections of wires used [mm²]: 1

Sound pressure [dB]: 38

Air-flow volume rate [m³/h]: 100

Motor-power consumption [W]: 19

IP class: X4

Protection class: II

LOGISTIC DATA:

Packaging method: 12

Number of units in the packaging: 12

Net unit weight [g]: 430

Grammage [g]: 550

Length of a unit pack [cm]: 14

Width of a unit pack [cm]: 13

Height of a unit pack [cm]: 11

Weight of a cardboard box [kg]: 6.6

Width of a cardboard box [cm]: 29.5

Height of a cardboard box [cm]: 28.5

Length of a cardboard box [cm]: 34

Volume of a cardboard box [m³]: 0.028586

Ducted fan

ADDITIONAL INFORMATION:

- Rotation speed: 2550/min
- Efficiency 100m³/h
- Noise level 38dB (A)
- CYKLON EOL100HT, additionally equipped with a moisture sensor which allows the fan to activate after reaching a pre-set moisture threshold