


In-ground fixture

5905339072801



Kanlux ROGER DL is a ground-recessed luminaire with a built-in LED module. The specific shape of the shade distributes light evenly, which produces a unique light effect. The luminaire has a very high rating of tightness (IP66) and resistance to mechanical damage (IK09).

### GENERAL DATA:

**Colour:** grey

**Place of assembly:** In the ground

**Place of application:** Indoors and outdoors

**Minimum distance from the illuminated object:** 0,1m

**Compatible with a dimmer:** no

**Fixture lighting direction:** horizontal

**Height [mm]:** 74

**Diameter [mm]:** 100

**Number of chokes:** 1

**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 1

**Class of protection against electric shock:** I

**Diode type:** LED DIP

**Colour temperature:** cold white

**Correlated colour temperature [K]:** 6000-6500

**Service life [h]:** 20000

**Ambient temperature range to which the product can be exposed:** -20÷35

**Enclosure material:** steel

**Panel/frame material:** aluminum alloy

**Protective glass material:** plastic

**Connection type:** Free cable ends

**Wire length [m]:** 0.3

**Wire diameter [mm<sup>2</sup>]:** 0,75

**Lamp-heating time [s]:** ≤1

**Lamp-ignition time [s]:** ≤0,5

**Permissible static pressure [kN]:** 5

**IK class:** 09

**IP class:** 66

In-ground fixture

### LOGISTIC DATA:

**Packaging method:** 24  
**Number of units in the secondary packaging:** 1  
**Number of units in the packaging:** 24  
**Net unit weight [g]:** 280  
**Grammage [g]:** 345.83  
**Length of a unit pack [cm]:** 10.5  
**Width of a unit pack [cm]:** 10.5  
**Height of a unit pack [cm]:** 9  
**Weight of a cardboard box [kg]:** 8.29992  
**Width of a cardboard box [cm]:** 22  
**Height of a cardboard box [cm]:** 37  
**Length of a cardboard box [cm] :** 32  
**Volume of a cardboard box [m<sup>3</sup>]:** 0.026048

### ADDITIONAL INFORMATION:

- Junction box included

KANLUX S.A. (kat 7280) ROGER DL-LED12 / Krzywa rozsytu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 7280) ROGER DL-LED12  
Lampy: 1 x ROGER DL-LED12

