


07281 ROGER DL-2LED6

In-ground fixture

5905339072818



Kanlux ROGER DL is a ground-recessed luminaire with a built-in LED module. The specific shape of the shade distributes light evenly, which produces a unique light effect. The luminaire has a very high rating of tightness (IP66) and resistance to mechanical damage (IK09).

GENERAL DATA:

Colour: grey

Place of assembly: In the ground

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,1m

Compatible with a dimmer: no

Fixture lighting direction: horizontal

Height [mm]: 74

Diameter [mm]: 100

Number of chokes: 1

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 1

Class of protection against electric shock: I

Diode type: LED DIP

Colour temperature: cold white

Correlated colour temperature [K]: 6000-6500

Service life [h]: 20000

Ambient temperature range to which the product can be exposed: -20÷35

Enclosure material: steel

Panel/frame material: aluminum alloy

Protective glass material: plastic

Connection type: Free cable ends

Wire length [m]: 0.3

Wire diameter [mm²]: 0,75

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

Permissible static pressure [kN]: 5

IK class: 09

IP class: 66

In-ground fixture



LOGISTIC DATA:

Packaging method: 24

Number of units in the secondary packaging: 1

Number of units in the packaging: 24

Net unit weight [g]: 270

Grammage [g]: 333.33

Length of a unit pack [cm]: 10

Width of a unit pack [cm]: 10.5

Height of a unit pack [cm]: 9

Weight of a cardboard box [kg]: 7.99992

Width of a cardboard box [cm]: 22

Height of a cardboard box [cm]: 37

Length of a cardboard box [cm]: 32

Volume of a cardboard box [m³]: 0.026048

ADDITIONAL INFORMATION:

- Junction box included

KANLUX S.A. (kat 7281) ROGER DL-2LED6 / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 7281) ROGER DL-2LED6
Lampy: 1 x ROGER DL-2LED6

