


07362 RADAN CT-DSO50

Ceiling-mounted spotlight fitting 5905339073624













Kanlux RADAN are simple eyes which will light up each room. You can choose a source of light and a version of the holder on your own - with adjustment or immovable.

GENERAL DATA:

Colour: aluminium

Necessity of using self-shielding lamps: yes Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m The product is not suitable to be installed on a normally

flammable surface: >35W

The product is not suitable to be covered with a heat-insulating

material: yes Height [mm]: 24 Diameter [mm]: 79

Assembly hole [mm]: Ø60-70

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC Maximum power [W]: max 10

Class of protection against electric shock: III

Light source: MR16 **Light source included**: no

Cap: Gx5,3

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: aluminum alloy Connection type: Free cable ends

Wire length [m]: 0.12 Wire diameter [mm²]: 0.75

Lighting-fixture angle regulation: none

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50

Number of units in the packaging: 50

Net unit weight [g]: 54 Grammage [g]: 83

Length of a unit pack [cm]: 8.5 Width of a unit pack [cm]: 4 Height of a unit pack [cm]: 8.5

Date of issue: 11.05.2023, 13:15

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





07362 RADAN CT-DSO50

Ceiling-mounted spotlight fitting



Weight of a cardboard box [kg]: 4.15
Width of a cardboard box [cm]: 22.5
Height of a cardboard box [cm]: 20
Length of a cardboard box [cm]: 45.5
Volume of a cardboard box [m³]: 0.020475

Date of issue: 11.05.2023, 13:15

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

