

08091 TUNA MINI N


Ceiling-mounted light fitting with replaceable light source

5905339080912

















Kanlux TUNA ceiling light fixture is a good choice for staircases, basements, attics and other such rooms. Proper level of protection against dust and moisture allows for its use both indoors and outdoors.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted, ceiling mounted Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes

Height [mm]: 104
Diameter [mm]: 200

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 25

Class of protection against electric shock: II

Lampshade material: glass Light source: GLS/CFL/LED Light source included: no Cap (Light source): E27

Ambient temperature range to which the product can be

exposed: -10÷35

Enclosure material: plastic

Connection type: Terminal block

Range of sections of wires used [mm²]: 1-1,5

IP class: 44

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 10


Number of units in the secondary packaging: 1


Number of units in the packaging: 10

Net unit weight [g]: 720 Grammage [g]: 786

Gross unit weight [g]: 828
Length of a unit pack [cm]: 20
Width of a unit pack [cm]: 10
Height of a unit pack [cm]: 10

Weight of a cardboard box [kg]: 7.86










08091 TUNA MINI N

Ceiling-mounted light fitting with replaceable light source

Width of a cardboard box [cm]: 40
Height of a cardboard box [cm]: 33
Length of a cardboard box [cm]: 40
Volume of a cardboard box [m³]: 0.0528



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

