


Bulkhead fixture

5905339080929









C€ ERE ĽK €€

Kanlux MILO is a classic channel luminaire used usually in technical rooms, garages, basements, staircases, corridors, etc. The luminaire has a metal (7040T) or plactic (7040T/P) protective mesh which protects the shade from mechanical damage.

GENERAL DATA:

Colour: black Place of assembly: wall mounted, ceiling mounted Place of application: Indoors and outdoors Minimum distance from the illuminated object: 0,5m Length [mm]: 165 Width [mm]: 100 Height [mm]: 110

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 60 Class of protection against electric shock: II Lampshade material: glass Light source: GLS/CFL/LED Cap: E27 Enclosure material: plastic Connection type: Terminal block Range of sections of wires used [mm²]: 1-1,5 IK class: 06 IP class: 54

LOGISTIC DATA:

Packaging method: 12 Number of units in the secondary packaging: 1 Number of units in the packaging: 12 Net unit weight [g]: 410 Grammage [g]: 441.67 Length of a unit pack [cm]: 18 Width of a unit pack [cm]: 13 Height of a unit pack [cm]: 12 Weight of a cardboard box [kg]: 5.30004 Width of a cardboard box [cm]: 18 Height of a cardboard box [cm]: 35 Length of a cardboard box [cm]: 48 Volume of a cardboard box [m³]: 0.03024





Bulkhead fixture

