


## **08550** DRIFT LED 3-18W

CV power supply unit

5905339085504













Kanlux DRIFT is an electronic constant-voltage power supply unit with power of 3-18 W or 0-6 W. It is used for powering LED belts such as LEDS P or LEDS B.

#### **GENERAL DATA:**

Colour: white

Place of application: Indoors

Possibility of installation on a normally flammable

surface: yes Length [mm]: 50 Height [mm]: 20

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 3-18

Class of protection against electric shock: ||

Material: plastic

Ambient temperature range to which the product can be

exposed: 5÷25

**Connection type**: Terminal block

Range of sections of wires used [mm $^2$ ]: 0,75 $\div$ 1,5

Supply-cord type: constant-voltage

Thermal protection: 110°C
Short-circuit protection: yes
Maximum temperature Ta [°C]: 50
Input voltage - PRI [V]: 220-240
Output voltage - SEC [V]: 12 DC
Output current - sec [ma]: max 1500

**IP class**: 20 **Tc [°C]**: 85

## LOGISTIC DATA:

Packaging method: 100


Number of units in the packaging: 100 Number of units per layer on a pallet: 800

Net unit weight [g]: 100 Grammage [g]: 119

Length of a unit pack [cm]: 5.5 Width of a unit pack [cm]: 2.5 Height of a unit pack [cm]: 15

Weight of a cardboard box [kg]: 11.9 Width of a cardboard box [cm]: 28 Height of a cardboard box [cm]: 23.5 Length of a cardboard box [cm]: 31.5










# **08550** DRIFT LED 3-18W

CV power supply unit

Volume of a cardboard box [m³]: 0.020727

#### ADDITIONAL INFORMATION:

- Voltage stabilization 12V DC
- Built-in circuit and overload protection
- DRIFT LED 0-6W and 0-30W are provided with 0.75mm2 cable 15cm length / DRIFT LED 3-18W connection via terminals 0.5-1.5mm2



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

