


08810 PIRES DL-600

Ceiling-mounted light fitting with replaceable light source

5905339088109



Kanlux PIRES is a ceiling light fixture with minimalistic appearance which can be used outside too thanks to IP44 degree of tightness. To increase comfort, we also propose versions equipped with a microwave motion detector (code 19000 and 8810) the range of which comes to 9 metres.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Micro-interval between relay contacts: yes

Minimum distance from the illuminated object: 0,5m

Wykrywanie ruchu: yes

Height [mm]: 105

Diameter [mm]: 275

Sensitivity regulation: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: max 60

Class of protection against electric shock: II

Lampshade material: glass

Light source: GLS/CFL/LED

Light source included: no

Cap: E27

Ambient temperature range to which the product can be exposed: 5÷35

Enclosure material: plastic

Sensor type: microwave

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1-2,5

Sensor-operation time [second-minute]: 8-12

Sensor-operation frequency [MHz]: 5800

sensor working angle [°]: H360/V180

Illumination-level setpoint by which the sensor detects movement [lx]: 2-2000

IP class: 44

Sensor range[m]: max 12

Ceiling-mounted light fitting with replaceable light source



LOGISTIC DATA:

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1480

Grammage [g]: 1864

Length of a unit pack [cm]: 32

Width of a unit pack [cm]: 12.5

Height of a unit pack [cm]: 32

Weight of a cardboard box [kg]: 9.32

Width of a cardboard box [cm]: 33

Height of a cardboard box [cm]: 34

Length of a cardboard box [cm]: 67

Volume of a cardboard box [m³]: 0.075174

ADDITIONAL INFORMATION:

- provided with a MW motion sensor
- maximum horizontal adjustment range for the motion sensor: 360°
- maximum vertical motion sensor angle: 140°
- lighting time adjustable in the range of 8 s to 12 min
- maximum motion detection range: 9 m
- motion detection 0.3...3 m/s (1...10 km/h), sensitivity adjustment range: 2...2,000 lx

KANLUX S.A. (kat 8810) PIRES DL-600 / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 8810) PIRES DL-600
Lampy: 1 x A60 60W/c

