


08981 JURBA DL-218L

Ceiling-mounted light fitting with replaceable light source

5905339089816



Kanlux JURBA is a hermetic ceiling light fixture of excellent workmanship. The fixture can be mounted both on ceilings and on walls, indoors and outdoors. The increased protection rating IP44 of Kanlux JURBA luminaires protects them from dust, particles and moisture.

GENERAL DATA:

Colour: nickel satin

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Length [mm]: 285

Width [mm]: 285

Height [mm]: 85

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 2 x max 18

Class of protection against electric shock: II

Lampshade material: PC

Light source: CFL/LED

Light source included: no

Cap: E27

Ambient temperature range to which the product can be exposed: -10÷35

Enclosure material: steel

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1-2,5

IK class: 10

IP class: 44

LOGISTIC DATA:

Packaging method: 8

Number of units in the secondary packaging: 1

Number of units in the packaging: 8

Net unit weight [g]: 1650

Grammage [g]: 1925

Length of a unit pack [cm]: 29

Width of a unit pack [cm]: 9

Height of a unit pack [cm]: 29

Weight of a cardboard box [kg]: 15.4

Width of a cardboard box [cm]: 39

Height of a cardboard box [cm]: 31.5

Length of a cardboard box [cm]: 59.5

Ceiling-mounted light fitting with replaceable light source



Volume of a cardboard box [m³]: 0.073096

KANLUX S.A. (kat 8981) JURBA DL-218L / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 8981) JURBA DL-218L
Lampy: 2 x TC-DSE 18W/827

