

## 19000 PIRES ECO DL-250

Ceiling-mounted light fitting with replaceable light source

5905339190000



Kanlux PIRES is a ceiling light fixture with minimalist appearance which can be used outside too thanks to IP44 degree of tightness. To increase comfort, we also propose versions equipped with a microwave motion detector (code 19000 and 8810) the range of which comes to 9 metres.

### PRODUCT PARAMETERS:

**Colour:** white

**Place of assembly:** wall mounted, ceiling mounted

**Place of application:** Indoors and outdoors

**Micro-interval between relay contacts:** yes

**Minimum distance from the illuminated object:** 0,5m

**Wykrywanie ruchu:** yes

**Light source included:** no

**Height [mm]:** 110

**Diameter [mm]:** 277

**Sensitivity regulation:** yes

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** max 25

**Class of protection against electric shock:** II

**Lampshade material:** plastic

**Light source:** CFL/LED

**Cap:** E27

**Ambient temperature range to which the product can be exposed:** 5÷35

**Enclosure material:** plastic

**Sensor type:** microwave

**Connection type:** Bolt terminal block

**Range of sections of wires used [mm<sup>2</sup>]:** 1-2,5

**Sensor-operation time [second-minute]:** 8-12

**Sensor-operation frequency [MHz]:** 5800

**sensor working angle [°]:** H360/V180

**Illumination-level setpoint by which the sensor detects movement [lx]:** 2-2000

**IP class:** 44

**Sensor range[m]:** max 9

### LOGISTIC DATA:

**Packaging method:** 5

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 5


**Net unit weight [g]:** 530

**Grammage [g]:** 852

**Length of a unit pack [cm]:** 28

## 19000 PIRES ECO DL-250

Ceiling-mounted light fitting with replaceable light source



**Width of a unit pack [cm]:** 11.5  
**Height of a unit pack [cm]:** 28  
**Weight of a cardboard box [kg]:** 4.26  
**Width of a cardboard box [cm]:** 30.5  
**Height of a cardboard box [cm]:** 36.1  
**Length of a cardboard box [cm]:** 59  
**Volume of a cardboard box [m³]:** 0.064962

### ADDITIONAL INFORMATION:

- provided with a MW motion sensor
- maximum horizontal adjustment range for the motion sensor: 360°
- maximum vertical motion sensor angle: 180°
- lighting time adjustable in the range of 8 s to 12 min
- maximum motion detection range: 9 m
- motion detection 0.3...3 m/s (1...10 km/h), sensitivity adjustment range: 2...2,000 lx



KANLUX S.A. (kat 19000) PIRES ECO DL / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 19000) PIRES ECO DL  
Lampy: 1 x TC-QSE 15W/827 SUPERSHAP

