


22370 AZ-10A TH 35

TH35 rail-mounted twilight sensor

5905339223708



Kanlux AS-10 is a dusk and dawn light switch system. It is used for turning on and turning off lighting circuits or other electric receivers, depending on the natural light intensity level (day/night).

PRODUCT PARAMETERS:

Hysteresis: 20Lx

Colour: white

Place of assembly: rail TH35

Place of application: Indoors and outdoors

Norm: EN60730-1; PN-EN 62052-11

Length [mm]: 35

Width [mm]: 66

Height [mm]: 90

Rated voltage [V]: 220-240 AC

Rated current [A]: 10

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Ambient temperature range to which the product can be exposed: -20÷40

Maximum load [W]: 2300

IP class: 20/65

LOGISTIC DATA:

Packaging method: 100

Number of units in the secondary packaging: 1

Number of units in the packaging: 100

Net unit weight [g]: 130

Grammage [g]: 171.4

Length of a unit pack [cm]: 10

Width of a unit pack [cm]: 5.5

Height of a unit pack [cm]: 7.5

Weight of a cardboard box [kg]: 17.14

Width of a cardboard box [cm]: 33

Height of a cardboard box [cm]: 32.5

Length of a cardboard box [cm]: 51.5

Volume of a cardboard box [m³]: 0.055234

IDEAL^{TS}

by **Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

22370 AZ-10A TH 35

TH35 rail-mounted twilight sensor