


23132 KSD-T2 275/120 3P

Surge protector

5905339231321



Varistor surge arrester, class 2 (T2/C): is used to protect LV power installations against effects of induced and switching surges / in buildings without lightning protection and with cable connection, the arrester provides sufficient protection without the need for mounting class 1 arresters (T1/B). Spike arresters, class II, Type 2 (group C). KSD-T2 class II surge arresters (SPD) are made in accordance with EN61643-1. These type 1+2 surge arresters are designed to protect low voltage installations against indirect atmospheric discharges and switching surges in the grid. Arresters provide protection in the 1-2 zone in accordance with EN62305 standard.

PRODUCT PARAMETERS:

Place of assembly: na szynę TH35

Place of application: Indoors

Norm: PN-EN61643-1

Width [mm]: 52.5

Height [mm]: 91

Depth [mm]: 68

Number of fields: 3

Rated voltage [V]: 230 AC

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -5÷40

Connection type: Terminal block

Protection type: T2 (C)

Number of modules: 3

The highest voltage of continuous operation U(c): 275V

The highest discharge power I_{max}: 40kA

Voltage protection level U(p): ≤1,3kV

Residual current I(pe): 30μA

Transitory current-strength increase [kA]: 40

Expected short-circuit current I_{fi} [A] r.m.s.: 100

IP class: 20

Relative humidity range: 5÷95

Rated discharge current I_n [kA]: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 4

Number of units in the secondary packaging: 4

Number of units in the packaging: 56

23132 KSD-T2 275/120 3P

Surge protector

Net unit weight [g] : 290

Grammage [g] : 351.79

Length of a unit pack [cm] : 10.5

Width of a unit pack [cm] : 6

Height of a unit pack [cm] : 7

Weight of a cardboard box [kg] : 19.70024

Width of a cardboard box [cm] : 50

Height of a cardboard box [cm] : 50

Length of a cardboard box [cm] : 50

Volume of a cardboard box [m³] : 0.125