


23183 KRD6-4/25/30

Residual-current circuit breaker, 4P

5905339231833



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

PRODUCT PARAMETERS:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61008-1

Length [mm]: 75

Width [mm]: 70

Height [mm]: 82

Rated voltage [V]: 400 AC

Rated current [A]: 25

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: do 35

Residual-current protection type: AC

Number of modules: 4

Differential-rated current [mA]: 30

IP class: 20

Rated insulation voltage UI [V]: 400

Number of poles: 4

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 30

Number of units in the secondary packaging: 1

Number of units in the packaging: 30

Net unit weight [g]: 340

Grammage [g]: 390.67

Gross unit weight [g]: 376

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 8

Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 11.7201

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 18.5

Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.024346