


## 23186 KRD6-2/16/10

Residual-current circuit breaker, 2P

5905339231864



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

### PRODUCT PARAMETERS:

**Colour:** white

**Place of assembly:** na szynę TH35

**Norm:** PN-EN 61008-1

**Length [mm]:** 75

**Width [mm]:** 35

**Height [mm]:** 81

**Rated voltage [V]:** 230 AC

**Rated current [A]:** 16

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -25÷40

**Residual-current protection type:** AC

**Number of modules:** 2

**Differential-rated current [mA]:** 10

**IP class:** 20

**Rated insulation voltage UI [V]:** 400

**Number of poles:** 2

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 60

**Number of units in the secondary packaging :** 1

**Number of units in the packaging:** 60

**Net unit weight [g]:** 210

**Grammage [g]:** 242.33

**Gross unit weight [g]:** 240

**Length of a unit pack [cm]:** 9

**Width of a unit pack [cm]:** 4.5

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 14.5398

**Width of a cardboard box [cm]:** 28

**Height of a cardboard box [cm]:** 18.5

**Length of a cardboard box [cm]:** 47

**Volume of a cardboard box [m³]:** 0.024346