

## 23193 KRD6-4/63/30-A

Residual-current circuit breaker, 4P

5905339231932



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

### PRODUCT PARAMETERS:

**Rated voltage [V]:** 400 AC

**Rated frequency [Hz]:** 50

**Rated current [A]:** 63

**Differential-rated current [mA]:** 30

**Residual-current protection type:** A

**Colour:** white

**Place of assembly:** na szynę TH35

**IP class:** 20

**Norm:** PN-EN 61008-1

**Length [mm]:** 75

**Width [mm]:** 70

**Height [mm]:** 82

**Ambient temperature range to which the product can be exposed:** -25÷40

**Range of sections of wires used [mm<sup>2</sup>]:** do 35

**Terminal capacity – solid conductor [mm<sup>2</sup>]:** max 25

**Terminal capacity – stranded conductor [mm<sup>2</sup>]:** max 16

**Number of modules:** 4

**Rated activation capacity[A]:** 6000

**Rated insulation voltage UI [V]:** 400

**Number of poles:** 4

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 30

**Number of units in the secondary packaging :** 1



**Number of units in the packaging :** 30

**Net unit weight [g]:** 340

**Grammage [g]:** 390.67

**Gross unit weight [g]:** 382

**Length of a unit pack [cm]:** 9



Date of issue: 15.12.2025, 15:25

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

## 23193 KRD6-4/63/30-A

Residual-current circuit breaker, 4P

<b>Width of a unit pack [cm]:</b>	8
<b>Height of a unit pack [cm]:</b>	8
<b>Weight of a cardboard box [kg]:</b>	11.7201
<b>Width of a cardboard box [cm]:</b>	28
<b>Height of a cardboard box [cm]:</b>	18.5
<b>Length of a cardboard box [cm] :</b>	47
<b>Volume of a cardboard box [m<sup>3</sup>]:</b>	0.024346

Date of issue: 15.12.2025, 15:25

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com