


23198 KRD6-4/100/30-A

Residual-current circuit breaker, 4P

5905339231987



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

PRODUCT PARAMETERS:

Rated voltage [V]: 400 AC

Rated frequency [Hz]: 50

Rated current [A]: 100

Differential-rated current [mA]: 30

Residual-current protection type: A

Colour: white

Place of assembly: na szynę TH35

IP class: 20

Norm: PN-EN 61008-1

Length [mm]: 75

Width [mm]: 70

Height [mm]: 82

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: do 35

Terminal capacity – solid conductor [mm²]: max 25

Terminal capacity – stranded conductor [mm²]: max 16

Number of modules: 4

Rated activation capacity[A]: 6000

Rated insulation voltage UI [V]: 400

Number of poles: 4

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 30

Number of units in the secondary packaging: 1

Number of units in the packaging: 30

Net unit weight [g]: 420

Grammage [g]: 390.67

Gross unit weight [g]: 416

Length of a unit pack [cm]: 9

23198 KRD6-4/100/30-A

Residual-current circuit breaker, 4P

| | |
|---|----------|
| Width of a unit pack [cm]: | 8 |
| Height of a unit pack [cm]: | 8 |
| Weight of a cardboard box [kg]: | 11.7201 |
| Width of a cardboard box [cm]: | 28 |
| Height of a cardboard box [cm]: | 18.5 |
| Length of a cardboard box [cm] : | 47 |
| Volume of a cardboard box [m³]: | 0.024346 |

Date of issue: 15.12.2025, 15:22

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com