


23213 KRO6-2/B10/30

Residual-current circuit breaker with overcurrent module, 6kA, 2P

5905339232137



Residual current device with overcurrent protection is used to protect against overloads and short circuits in installations and devices, as well as to protect against electric shock.

PRODUCT PARAMETERS:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61009 -1

Length [mm]: 75

Width [mm]: 35

Height [mm]: 81

Rated voltage [V]: 230 AC

Rated current [A]: 10

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: 10÷16

Residual-current protection type: AC

Release characteristics: B

Energy-limit class: 3

Number of modules: 2

Differential-rated current [mA]: 30

Rated short-circuit current [A]: 6000

IP class: 20

Rated insulation voltage UI [V]: 400

Number of poles: 2

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 60

Number of units in the secondary packaging : 1

Number of units in the packaging: 60

Net unit weight [g]: 180

Grammage [g]: 212.33

Gross unit weight [g]: 212

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 4

Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 12.7398

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 18.5

23213 KRO6-2/B10/30

Residual-current circuit breaker with overcurrent module, 6kA, 2P

Length of a cardboard box [cm] : 47

Volume of a cardboard box [m³] : 0.024346