


## 23235 KMI-3/100A

Modular switch disconnector

5905339232359



Switch disconnector is used to disconnect circuits loaded with rated current.

### PRODUCT PARAMETERS:

**Utilisation category:** AC-22A

**Colour:** white

**Place of application:** Indoors

**Norm:** PN-EN 60947-3

**Length [mm]:** 76

**Width [mm]:** 52.5

**Height [mm]:** 82

**Rated voltage [V]:** 230/400 AC

**Rated current [A]:** 100

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -25÷45

**Range of sections of wires used [mm<sup>2</sup>]:** 1÷50

**Number of modules:** 3

**IP class:** 20

### LOGISTIC DATA:

**Packaging method:** 4

**Number of units in the secondary packaging:** 4

**Number of units in the packaging:** 40

**Net unit weight [g]:** 250

**Grammage [g]:** 280

**Length of a unit pack [cm]:** 5.5

**Width of a unit pack [cm]:** 7.5

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 11.2

**Width of a cardboard box [cm]:** 25

**Height of a cardboard box [cm]:** 19.5

**Length of a cardboard box [cm]:** 45

**Volume of a cardboard box [m<sup>3</sup>]:** 0.021938