


## 23241 KMC-20-40

Modular contactor, 230 VAC control voltage

5905339232410



Contactor is used for automatic activation of electricity receivers. Categories of use AC7a, AC7b.

### PRODUCT PARAMETERS:

**Utilisation category:** AC-7A, AC-7B

**Colour:** white

**Place of assembly:** rail TH35

**Place of application:** Indoors

**Norm:** PN-EN 60947-4-1

**Rated voltage [V]:** 230 AC

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -25÷40

**Connection type:** Terminal block

**Number of n.o./n.c. contacts:** 4/0

**Number of modules:** 2

**Rated power AC-7A/400:** 13kW

**Rated power AC-7B/400:** 3,5kW

**Coil-supply voltage [V]:** 230V AC 50/60Hz

**Rated current I(N) AC-7A/AC-1:** 20A

**Rated current I(N) AC-7B/AC-1:** 7A

**IP class:** 20

### LOGISTIC DATA:

**Packaging method:** 6

**Number of units in the secondary packaging:** 6

**Number of units in the packaging:** 60

**Net unit weight [g]:** 210

**Grammage [g]:** 230

**Length of a unit pack [cm]:** 3.5

**Width of a unit pack [cm]:** 7.5

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 13.8

**Width of a cardboard box [cm]:** 28

**Height of a cardboard box [cm]:** 18.5

**Length of a cardboard box [cm]:** 47

**Volume of a cardboard box [m<sup>3</sup>]:** 0.024346

**IDEAL**<sup>TS</sup>

by **Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

**23241 KMC-20-40**

---

Modular contactor, 230 VAC control voltage