


23242 KMC-63-40

Modular contactor, 230 VAC control voltage

5905339232427



Contactor is used for automatic activation of electricity receivers. Categories of use AC7a, AC7b.

PRODUCT PARAMETERS:

Utilisation category: AC-7A, AC-7B

Colour: white

Place of assembly: rail TH35

Place of application: Indoors

Norm: PN-EN 60947-4-1

Rated voltage [V]: 230 AC

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Connection type: Terminal block

Number of n.o./n.c. contacts: 4/0

Number of modules: 3

Rated power AC-7A/400: 40kW

Rated power AC-7B/400: 13kW

Coil-supply voltage [V]: 230V AC 50/60Hz

Rated current I(N) AC-7A/AC-1: 63A

Rated current I(N) AC-7B/AC-1: 25A

IP class: 20

LOGISTIC DATA:

Packaging method: 4

Number of units in the secondary packaging: 4

Number of units in the packaging: 40

Net unit weight [g]: 320

Grammage [g]: 350

Length of a unit pack [cm]: 5.5

Width of a unit pack [cm]: 7

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 14

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 18.5

Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.024346

IDEAL^{TS}

by **Kanlux**

ul. Objazdowa 1-3, 41-922 Radzionków, Poland

23242 KMC-63-40

Modular contactor, 230 VAC control voltage